

Dead Zone Eliminator®

OTDR Launch Cable / Test Box

Series 5 Carry Case

Launch Lead



Features / Benefits

- Use as a Pulse Suppressor, OTDR Launch Cable, Delay Line, Training, Product Demonstrations, Calibration
- Prevents fiber damage and stress during use or transportation
- Rugged Carry Case
- Portable for field use
- Custom length configurations available for OTDR applications
- Singlemode, Multimode 62.5/125, Multimode 50/125 OM2 and Multimode 50/125 OM3
- Connectors meet or exceed Telcordia Specifications

Applications

- OTDR Launch Cable/Lead
- Equipment Calibration
- System emulation of loss, length, time delay and reflectance

Description

The Dead Zone Eliminator® is designed to aid in the testing of fiber optic cable when using an OTDR to help minimize the effects of the OTDR's launch pulse on measurement uncertainty.

Units are available in any length up to 5 km and housed in a rugged, airtight, watertight carry case.

Simply specify the fiber type required, length and connector choice for the input and output lead. Standard lead length is 2 meters.


Dead Zone Eliminator®

OTDR Launch Box - Series 5

Specifications

Series 5 Dead Zone Eliminator® OTDR Launch Box

<i>Dimensions</i>	Length 8.7", Width 7.5", Height 3.9"
<i>Material</i>	SR Polypropylene
<i>Fiber Length (m)</i>	Up to 5000
<i>Fiber Types</i>	Singlemode 9/125, Multimode 62.5/125, Multimode 50/125 OM2, Multimode 50/125 OM3
<i>Lead Length</i>	2 Meters, 3mm buffer
<i>Insertion Loss</i>	<0.3 dB/km typical, <0.5 dB/km max
<i>Back Reflection (RL)</i>	<-55 dB
<i>Mating Reliability</i>	<.2 dB
<i>Connector Geometries</i>	All connectors meet or exceed Telcordia GR-326 Core Specification. <i>Apex Offset:</i> 0-50um <i>Radius of Curvature</i> 7-25 nm <i>Fiber Height</i> -50 to 50 mm <i>Fiber Roughness</i> 0-25 nm <i>Ferrule Roughness</i> 0-50 nm
<i>Storage Temp.</i>	-40° to +85° C
<i>Operating Temp.</i>	-40° to +85° C
<i>Humidity</i>	0 to 95%, non-condensing
<i>Weight</i>	1.5 lbs (w/out fiber)
<i>Warranty*</i>	1 year



Part Number Table

The Dead Zone Eliminator® is available with Singlemode 9/125, Multimode 62.5/125, Multimode 50/125 OM2 and Multimode 50/125 OM3 fiber. The diagram shown below displays the part number template for ordering. Please choose the **Connector Code** for the leads (input and output), **Fiber Code** for the type of fiber you require and the **Length** (in meters). For example, a 1000 meter singlemode unit with FC connectors on both leads would be D5151-S1000. Standard lead length is 2 meters.

D5 _ **5** _ - _ _ _ _ _ _ _ _ _
Input **Output** **Fiber** **Length / Meters**
Lead **Lead**

Connector Styles/Codes for leads:

1 - FC/UPC 5 - SC/APC
2 - ST®/UPC 7 - LC/UPC
3 - SC/UPC Y - E2000/UPC
4 - FC/APC Z - E2000/APC

Fiber:

S - Singlemode
M - Multimode 62.5/125
B - Multimode 50/125 OM2
C - Multimode 50/125 OM3



© 2011 Fiber Plus International. All rights reserved. Rev. 120111. Dead Zone Eliminator is a registered trademark of Fiber Plus International. *1 year warranty covers any manufacturing defects. Connector and lead replacement due to use are not covered under warranty. Products protected by numerous US and international patents and patents pending. Fiber Plus Intl reserves the right to improve, enhance or modify the features and specifications of products without prior notification.